

ioPAC 6500 Series (65M) Backplane Modules

Backplane modules for modular programmable IIN controllers



Features and Benefits

- Tool-free hardware installation and hot-swap design for maximizing operation efficiency
- Fully modular design for maximum deployment flexibility
- 2 x 2 pin grid design to prevent erroneous installations

Certifications




Introduction

The ioPAC 6500 Series (also referred to as Intelligent Integrated Node or IIN) is an advanced Linux-based RTU featuring a built-in Layer-2 managed switch. Equipped with an Arm Cortex-A53 quad-core CPU, the ioPAC 6500 Series delivers robust performance.


Error-proof Design—2 x 2 Pin Grid

The backplane module need to be assembled in the sequence: PWR > COM > CPU > EXP > IO. The 2 x 2 pin grid ensures that there is no error during installation and the correct assembly sequence is used.



Fully Modular Design

The ioPAC 6500 Series features a unique Lego-like mechanical design that allows for flexible deployment while minimizing installation efforts. The series can be divided into the components: Backplane modules, power modules, communication modules, expansion modules, CPU modules, I/O modules, and terminal-block modules.



Specifications

Power Parameters

Power Consumption	65M-BMIO02: 0.093 A @ 12 VDC 65M-BMIO04: 0.117 A @ 12 VDC
-------------------	--

Physical Characteristics

Slots	65M-BMPW01-CT-T: 1 (for power module) 65M-BMPW02-CT-T: 2 (for power modules) 65M-BMCM01-CT-T: 1 (for communication module) 65M-BMCM02-CT-T: 2 (for communication modules) 65M-BMCP01-CT-T: 1 (for CPU module) 65M-BMCP02-CT-T: 2 (for CPU modules) 65M-BMIO02-CT-T: 2 (for IO modules) 65M-BMIO04-CT-T: 4 (for IO modules) 65M-BMEXP01-CT-T: 1 (for expansion module) 65M-BMEXP02-CT-T: 2 (for expansion module)
Housing	Plastic
Dimensions	65M-BMPW01-CT-T/BMCM01-CT-T/BMCP01-CT-T/65M-BMEXP01-CT-T: 43 x 177 x 45.5 mm (1.69 x 6.97 x 1.79 in) 65M-BMPW02-CT-T/BMCM02-CT-T/BMCP02-CT-T/BMIO02-CT-T/65M-BMEXP02-CT-T: 86 x 177 x 45.5 mm (3.39 x 6.97 x 1.79 in) 65M-BMIO04-CT-T: 172 x 177 x 45.5 mm (6.77 x 6.97 x 1.79 in)
Weight	65M-BMPW01-CT-T: 162 g (0.36 lb) 65M-BMPW02-CT-T: 320 g (0.71 lb) 65M-BMCM01-CT-T: 169 g (0.37 lb) 65M-BMCM02-CT-T: 330 g (0.73 lb) 65M-BMCP01-CT-T: 170 g (0.37 lb) 65M-BMCP02-CT-T: 325 g (0.72 lb) 65M-BMIO02-CT-T: 205 g (0.45 lb) 65M-BMIO04-CT-T: 395 g (0.87 lb) 65M-BMEXP01-CT-T: 173 g (0.38 lb) 65M-BMEXP02-CT-T: 322 g (0.71 lb)
Installation	DIN-rail mounting Rack mounting (with optional kit)

Environmental Limits

Operating Temperature	-40 to 75°C (-40 to 167°F) Note: Proper airflow is required in an environment with temperature > 65°C
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)
Altitude	2000 m ¹

Standards and Certifications

EMC	EN 55032/35 EN 61000-6-2/-6-4
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: (DC) 1 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: (DC) 0.5 kV L-N, 1 kV L/N-PE; Signal: 1 kV; IO: 0.5 kV IEC 61000-4-6 CS: Power: 10 V; Signal: 10 Vrms IEC 61000-4-8 PFMF: 30 A/m
Safety	UL 61010-1 UL 61010-2-201
Shock	IEC 60068-2-27 Half sine wave; acceleration: 15 g; time: 11 ms
Vibration	IEC 60068-2-6 DIN-rail mounted: 7 mm peak-peak (p-p) (2 to 8.42 Hz), 1 g (8.42 to 150 Hz) Rack mounted (with optional kit): 7 mm peak-peak (p-p) (2 to 8.42 Hz), 0.5 g (8.42 to 150 Hz)
Package Vibration Test	ISTA 1A
Package Drop Test	ISTA 1A

MTBF

Time	65M-BMPW01-CT-T: 1,130,092,735 hrs 65M-BMPW02-CT-T: 1,382,748,219 hrs 65M-BMCM01-CT-T: 1,856,744,727 hrs 65M-BMCM02-CT-T: 1,856,744,727 hrs 65M-BMCP01-CT-T: 5,032,783,357 hrs 65M-BMCP02-CT-T: 3,554,206,267 hrs 65M-BMIO02-CT-T: 6,140,939 hrs 65M-BMIO04-CT-T: 6,124,471 hrs 65M-BMEXP01-CT-T: 1,856,744,727 hrs 65M-BMEXP02-CT-T: 1,856,744,727 hrs
Standards	Telcordia Standard SR-332

Warranty

Warranty Period	5 years
Details	See www.moxa.com/warranty

Package Contents


Device	1 x ioPAC 6500 Series (65M) Backplane Module
Documentation	1 x quick installation guide 1 x warranty card

1. Please contact Moxa if you require products guaranteed to function properly at higher altitudes.

Dimensions


65M-BMPW01-CT-T

Unit: mm (inch)




65M-BMPW02-CT-T

Unit: mm (inch)




65M-BMCPU01-CT-T

Unit: mm (inch)




65M-BMCPU02-CT-T

Unit: mm (inch)




65M-BMCM01-CT-T

Unit: mm (inch)




65M-BMCM02-CT-T

Unit: mm (inch)




65M-BMEXP01-CT-T

Unit: mm (inch)




65M-BMEXP02-CT-T

Unit: mm (inch)




65M-BMIO02-CT-T

Unit: mm (inch)



65M-BMIO04-CT-T

Unit: mm (inch)



Ordering Information

Model Name	Slots	Module Supported	Conformal Coating	Operating Temperature
65M-BMPW01-CT-T	1	Power	Yes	-40 to 75°C
65M-BMPW02-CT-T	2	Power	Yes	-40 to 75°C
65M-BMCM01-CT-T	1	Communication	Yes	-40 to 75°C
65M-BMCM02-CT-T	2	Communication	Yes	-40 to 75°C
65M-BMCPU01-CT-T	1	CPU	Yes	-40 to 75°C
65M-BMCPU02-CT-T	2	CPU	Yes	-40 to 75°C

Model Name	Slots	Module Supported	Conformal Coating	Operating Temperature
65M-BMIO02-CT-T	2	IO	Yes	-40 to 75°C
65M-BMIO04-CT-T	4	IO	Yes	-40 to 75°C
65M-BMEXP01-CT-T	1	Expansion	Yes	-40 to 75°C
65M-BMEXP02-CT-T	2	Expansion	Yes	-40 to 75°C

© Moxa Inc. All rights reserved. Updated Sep 22, 2025.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.